

```
chandan@chandan-laptop:~$ cat /etc/fstab
# /etc/fstab: static file system information.
#
# Use 'blkid -o value -s UUID' to print the universally unique identifier
# for a device; this may be used with UUID= as a more robust way to name
# devices that works even if disks are added and removed. See fstab(5).
#
# <file system> <mount point> <type> <options> <dump> <pass>
proc /proc proc nodev,noexec,nosuid 0 0
# / was on /dev/sda5 during installation
UUID=98ced8cf-bd75-46ca-818f-d804b207f015 / ext3 errors=remount-ro 0 1
# /dos was on /dev/sda3 during installation
UUID=981D-145D /dos vfat defaults,umask=007,gid=46 0 1
# /windows was on /dev/sda4 during installation
UUID=CFA2-0591 /windows vfat defaults,umask=007,gid=46 0 1
# swap was on /dev/sda6 during installation
UUID=4156d470-91a5-4b45-81cc-a25761bddee7 none swap sw 0 0
chandan@chandan-laptop:~$
```

```
chandan@chandan-laptop:~$ mount
/dev/sda5 on / type ext3 (rw,errors=remount-ro)
proc on /proc type proc (rw,noexec,nosuid,nodev)
none on /sys type sysfs (rw,noexec,nosuid,nodev)
none on /sys/fs/fuse/connections type fusectl (rw)
none on /sys/kernel/debug type debugfs (rw)
none on /sys/kernel/security type securityfs (rw)
none on /dev type devtmpfs (rw,mode=0755)
none on /dev/pts type devpts (rw,noexec,nosuid,gid=5,mode=0620)
none on /dev/shm type tmpfs (rw,nosuid,nodev)
none on /var/run type tmpfs (rw,nosuid,mode=0755)
none on /var/lock type tmpfs (rw,noexec,nosuid,nodev)
none on /lib/init/rw type tmpfs (rw,nosuid,mode=0755)
binfmt_misc on /proc/sys/fs/binfmt_misc type binfmt_misc (rw,noexec,nosuid,nodev)
gvfs-fuse-daemon on /home/chandan/.gvfs type fuse.gvfs-fuse-daemon
(rw,nosuid,nodev,user=chandan)
chandan@chandan-laptop:~$
```